

19" Wall-Mounting Cabinet, 1-part




| Art.-No. | U | Height | Weight |
|--|-----|--------|---------|
| Depth 400 mm / Width 600 mm / max. load 50 kg | | | |
| 691704 | 4U | 240 mm | 13.0 kg |
| 691706 | 6U | 330 mm | 16.5 kg |
| 691709 | 9U | 465 mm | 20.5 kg |
| 691712 | 12U | 600 mm | 21.5 kg |
| 691715 | 15U | 730 mm | 25.0 kg |
| 691718 | 18U | 860 mm | 30.0 kg |
| 691721 | 21U | 997 mm | 31.0 kg |
| Depth 500 mm / Width 600 mm / max. load 50 kg | | | |
| 691704.1 | 4U | 240 mm | 18.0 kg |
| 691706.1 | 6U | 330 mm | 21.5 kg |
| 691709.1 | 9U | 465 mm | 25.5 kg |
| 691712.1 | 12U | 600 mm | 26.5 kg |
| 691715.1 | 15U | 730 mm | 30.0 kg |
| 691718.1 | 18U | 860 mm | 35.0 kg |
| 691721.1 | 21U | 997 mm | 36.0 kg |
| Depth 600 mm / Width 600 mm / max. load 50 kg | | | |
| 691712.2 | 12U | 600 mm | 26.5 kg |
| 691715.2 | 15U | 730 mm | 35.0 kg |
| 691718.2 | 18U | 860 mm | 40.0 kg |
| 691721.2 | 21U | 997 mm | 41.0 kg |

Basic configuration:

- Steel sheet housing with welded frame
- Completely pre-assembled, self-ventilated
- Prepared for mounting fan units in top and bottom
- Inside 2 x 19" profile rails front sided galvanised, depth-adjustable
- Front door with window made of certified safety glass
- Front door lockable with latch
- Side walls removable for easy access
- Internal earthing of all cabinet sections
- Cable infeed optionally from above or below, pre-punched openings
- Paint finish: RAL7035, light grey
- Degree of protection IP 20
- Supplied: 1 x brush terminal, 1 x set of captive nuts (PU 20 pcs.), 2 x key
- Delivery in transport packaging, from 30 kg / 12U on disposable pallet



inside view




top view



rear view

RoHS
compliant

| | | | |
|-----------------|------------------|--|---|
| Created MN | Date 02.11.10 | 19" Wall-Mounting Cabinet 1-part 6917XX.X | File: 6917XX.X_ENG |
| Last rev. MN | Date 02.11.10 | |  |